


# REMU EX 140 HD



## Dimensions

- A Width 126 cm
- B Depth 128 cm
- C Height 143 cm



## Weight

1680 kg

<b>For excavators</b>	16 – 21 tn
<b>Hydr.flow recommendation</b>	150 – 200 l/min
<b>Volume ISO/SAE</b>	0,9/1,1 m <sup>3</sup>
<b>Screening area</b>	0,9 m <sup>2</sup>
<b>Hydr. power continous/ peak</b>	50/100 kW
<b>Number of axles</b>	4
<b>Blade thickness and material</b>	16 mm Hardox 500
<b>Standard blade spacings</b>	25 mm (grain size 0-20 mm) 34 mm (grain size 0-29 mm) 50 mm (grain size 0-45 mm)

Working pressure 120 – 160 bar, max. pressure 310 bar.

**Main applications:** topsoil screening, producing quality soil and mixed materials, pipe back filling, screening demolition worksite waste materials, wood chip screening (and crushing) recycling materials, composting, aerating biomaterials, screening stones, soil, glass, metals, peat, bark, clay, bio waste, demolition waste

- Remu EX 140 HD is designed for very rough conditions. It can be used on soft and slippery surfaces with wet and clogging masses.
- Extremely wear resistant, the blades are thicker than in standard Remu models.
- Remu range includes buckets for 5-30 ton excavators, 2-20 ton wheel loaders, skid-steer/loaders and tractors.