


REMU EX 180



Dimensions

- A Width 151 cm
- B Depth 145 cm
- C Height 165 cm



Weight

2360 kg

For excavators	21 – 28 tn
Hydr.flow recommendation	150 – 200 l/min
Volume ISO/SAE	1,3/1,5 m ³
Screening area	1,4 m ²
Hydr. power continuous/ peak	50/70 kW
Number of axles	5
Blade thickness and material	10 mm Hardox 500
Standard blade spacings	20 mm (grain size 0-15 mm) 25 mm (grain size 0-20 mm) 32,5 mm (grain size 0-27 mm) 50 mm (grain size 0-45 mm)

Working pressure 120 – 160 bar, max. pressure 210 bar.

Main applications: topsoil screening, producing quality soil and mixed materials, pipe back filling, screening demolition worksite waste materials, wood chip screening (and crushing) recycling materials, composting, aerating biomaterials, screening stones, soil, glass, metals, peat, bark, clay, bio waste, demolition waste

- Remu EX 180 screening bucket is designed for rough conditions. The unique blade design eliminates clogging and makes the best result even in wet conditions when other methods have to stop.
- Easy transport and mobility to sites.
- Remu range includes buckets for 5-30 ton excavators, 2-20 ton wheel loaders, skid-steer/loaders and tractors.