


REMU EX 180 HD



Dimensions

- A** Width 151 cm
- B** Depth 145 cm
- C** Height 171 cm



Weight

2400 kg

For excavators	21 – 28 tn
Hydr.flow recommendation	150 – 200 l/min
Volume ISO/SAE	1,3/1,5 m ³
Screening area	1,4 m ²
Hydr. power continous/ peak	50/100 kW
Number of axles	5
Blade thickness and material	16 mm Hardox 500
Standard blade spacings	25 mm (grain size 0-20 mm) 34 mm (grain size 0-29 mm) 50 mm (grain size 0-45 mm)

Working pressure 120 – 160 bar, max. pressure 310 bar.

Main applications: topsoil screening, producing quality soil and mixed materials, pipe back filling, screening demolition worksite waste materials, wood chip screening (and crushing) recycling materials, composting, aerating biomaterials, screening stones, soil, glass, metals, peat, bark, clay, bio waste, demolition waste

- Remu EX 180 HD is designed for very rough conditions. It can be used on soft and slippery surfaces with wet and clogging masses.
- Extremely wear resistant, the blades are thicker than in standard Remu models.
- Remu range includes buckets for 5-30 ton excavators, 2-20 ton wheel loaders, skid-steer/loaders and tractors.