


REMU L 150



Dimensions

- A** Width 180 cm
- B** Depth 100 cm
- C** Height 105 cm



Weight

1030 kg

For excavators	10 – 14 tn
For wheel loaders skid-steers and tractors	4,5 – 6,5 tn *
Hydr.flow recommendation	60 – 100 l/min
Volume ISO/SAE	0,8/1,1 m ³
Screening area	1,0 m ²
Hydr. power continous/ peak	20/28 kW
Number of axles	3
Blade thickness and material	8 mm Hardox 500
Standard blade spacings	20 mm (grain size 0-15 mm) 27 mm (grain size 0-22 mm) 34,5 mm (grain size 0-30 mm) 48 mm (grain size 0-43 mm)

Working pressure 120 – 160 bar, max. pressure 210 bar.

* Please note when used with combination machines where back and front attachments are possible the recommended base machine weights can be higher

Main applications: topsoil screening, producing quality soil and mixed materials, pipe back filling, screening demolition worksite waste materials, wood chip screening (and crushing) recycling materials, composting, aerating biomaterials, screening stones, soil, glass, metals, peat, bark, clay, bio waste, demolition waste

- Remu L150 screening bucket is lightweight and compact in tight places like greenhouses and gardens
- The unique blade design eliminates clogging and makes the best result even in wet conditions when other methods have to stop.
- An universal tool for landscaping, fits in most front- and backyards
- Remu range includes buckets for 5-30 ton excavators, 2-20 ton wheel loaders, skid-steer/loaders and tractors.